

Wall Charger 2 Socketed


- Auto Solar Charging allowing you to utilise excess solar power to charge your EV, maximising the benefits of clean, renewable energy while reducing your energy bills.
- Tariff Sense Our energy management feature connects to any UK tariff, giving real-time insights and control over charging costs.
- Models with Wi-Fi/LAN, Wi-Fi/LAN/4G, Wi-Fi/LAN/4G+RFID
- Fully compliant with The Electric Vehicles (Smart Charge Points) Regulations 2021, including Schedule 1
- Full Smart functionality via Sync Energy App and OCPP 1.6J connectivity
- Dynamic charging up to 7.4 (32A)
- No earth rod required integrated open PEN conductor protection
- Safe integrated 30mA Type A RCD with 6mA DC
- OCPP 1.6J connectivity free lifetime over-the-air updates
- Type 2 socket with auto-lock
- Tethered version also available




PART NO.	DESCRIPTION	SOCKET TYPE	MAX OI (kw)	JTPUT (A)	INPUT VOLTAGE
EVWC2S7G-02	Single Phase 7.4KW / WI-FI / LAN	Type 2 with Autolock	7.4kW MODE 3	32A	220-240V
EVWC2S7GG-02	Single Phase 7.4KW / WI-FI / LAN / 4G	Type 2 with Autolock	7.4kW MODE 3	32A	220-240V
EVWC2S7GGR-02	Single Phase 7.4KW / WI-FI / LAN / 4G + RFID	Type 2 with Autolock	7.4kW MODE 3	32A	220-240V













ELECTRICAL SPECIFICATIONS						
MAXIMUM CHARGE CURRENT	Configura					

able, 6-32A LOAD BALANCING Supplied with Load Management Kit

OVERLOAD INPUT FREQUENCY 50-60hz AND FAULT Over current and over voltage protection PROTECTION

METER ACCURACY 2% Class C equivalent internal meter with option PEN FAULT Built-in. Earth Disconnection for connection to external RS485 MDBUS Meter

TERMINALS Combi screw first fix plug connector RCD PROTECTION Built-in 30mA AC Type A Protection

ELECTRICAL INDICATOR RGB LED and Buzzer Class 1 with Class 2(II) Housing CLASS

CONSUMER UNIT **INDICATOR MODES** BLUE - Standby, FLASHING BLUE - Preparing, 40A MCB or 30mA Type A RCD FLASHING GREEN - Finishing, SCROLLING GREEN **REQUIREMENTS** (Dependent on cable type &/or route) - Charging, YELLOW - No Network, RED - Error,

PURPLE - Balancer Error

2 Layer Protection, Bluetooth to Bluetooth CABLE ANTI-TAMPER Built-in cable wrap MANAGEMENT commissioning DETECTION

OPERATING CONDITIONS & CONSTRUCTION

OPERATING -25 to +55°C HOUSING UV Stabilised Polycarbonate

Base and Body RAL 9005 (Black) IP RATING IP65 COLOUR Trim RAL 9006 (Anthracite Grey) Optional Coloured Trims available as accessories

IK RATING IK10 DIMENSIONS $305 (H) \times 201 (W) \times 115 (D)$

Wall Mounted, 4-point with horizon-MOUNTING tal and vertical adjustment, 110mm x

145mm fixing centres

CONNECTIVITY & ACCESSORIES

SOC MODULE AI ESP32-S SOC SOFTWARE & Over-the-air FIRMWARE UPDATE

IEC61851-1, IEC61439-7, IEC 62955, IC 61851-21-2, WI-FI & ETHERNET 2.4Ghz 802.11 B/G/N & RJ45 STANDARDS & **APPROVALS** BS EN62196, EN301 511, EN 301 908-1/2/13, EN

301 489-3, EN 300 330, EMC COMPLIANT, CE, WI-FI SECURITY WPA/WPA2/WPA2-ENTERPRISE/WPS UKCA, The Electrical Vehicles (Smart Charge

Points) Regulations 2021 including schedule 1

BLUETOOTH 4.2 BR/EDR and BLE **SUPPLIED** 5 x Base Fixing Washers, 5 x Assembly ACCESSORIES Lid Bolts, 1 x Blanking Plug and 1 x 25mm

CONNECTION OCPP 1.6J Compression Gland, User-side Connector, Cord Grip and 2 x Cord Grip Assembly Screws, PROTOCOL 1 x RFID Key Fob (EVWC2S7GGR ONLY)*

4G DATA Model specific *Additional Key Fobs can be ordered using the 3 years included when used with code EVXRFIDFOB-01

> Top-up online to continue service after ACCESSORIES Single Charger Stand - (EVASTAND12S) 3 years. Twin Charger Stand - (EVASTAND12T)

Charging Cables - Various APP Powered by Sync Energy

Coloured Trims - Shown below



Anthracite Grey



EVWC2TPSR Signal Red



EVWC2TPSY Sandstone Yellow



Sync Energy (on the included package).

EVWC2TPRG Racing Green



EVWC2TPBG Blue Grey



EVWC2TPTW Traffic White



Jet Black



EVWC2TPSG Signal Grey



Deep Blue



EVWC2TMMS High Impact Metal

EVWC25xx.NH.111.2024